





TECNICAL INFORMATION

“Innovative permeable paver solutions are a necessity for the development of todays public spaces.” - Snøhetta


Asak
FLYT



ASAK FLYT 10
286x312x80 mm
Units per m²: 12,84
Weight per m²: 158,6kg



ASAK FLYT 17
286x312x80 mm
Units per m²: 12,84
Weight per m²: 148,3kg



ASAK FLYT 28
286x312x80 mm
Units per m²: 12,84
Weight per m²: 130,3kg

STANDARDS + PERFORMANCE

| | |
|---|--|
| Description: | The Asak FLYT collection consists of three hexagonal interlocking pavers that can be combined to create seamless transitions when designing and programming outdoor spaces. Asak FLYT is permeable paving and a part of SuDS (sustainable drainage system). The collection has a unique flexibility and allows for a fluent permeable gradient from 10 – 28%. Perfect for use in urban spaces. |
| Installation: | Must be installed according to correct guidance for permeable paving. |
| Area of use: | Public outdoor spaces; pavements, parks, squares, housing associations, schoolyards etc. |
| Colors: | Standard grey. Other colors request |
| Impregnation/ surface treatment: | Not standard. Can be ordered with ClearNOx treatment. ClearNOx is a photocatalytic coating that removes air pollution when the surface gets exposed to sun/daylight (UV). It also makes the surface clean by removing organic stains. Read more on www.asak.no |
| Frost resistance: | ≤1,0. Class 3 in according to NS-EN 1339, |
| Bending Strength: | 5,0Mpa class 3. This pressure applies to all sizes and depths. |
| Wear resistance: | ≤ 23 |
| Slip / Skid resistance: | 45 (Satisfactory) |